

## Combination Lamps Small Vehicle/Trailer

- Premium trailer lamps
- Shock, dust & water proof
- 5 Year warranty



### • Smallest LED combination lamp



Inactive

Active

#### Part Number

**81STI** - 12 Volt, Blister single

**81STIM** - Multivolt 12-24V, Blister single

|                  |                     |                 |                  |
|------------------|---------------------|-----------------|------------------|
| <b>Function</b>  | Stop/Tail/Indicator |                 |                  |
| <b>Size</b>      | 81mm x 81mm x 24mm  |                 |                  |
| <b>Voltage</b>   | 12 Volt or 24 Volt  |                 |                  |
| <b>LED Qty</b>   | 12                  |                 |                  |
| <b>Cable</b>     | 30cm cable          |                 |                  |
| <b>Draw</b>      | <b>Stop</b>         | <b>Tail</b>     | <b>Indicator</b> |
| <b>@13.8V</b>    | 0.12A               | 0.11A           | 0.02A            |
| <b>@28V</b>      | 0.07A               | 0.07A           | 0.03A            |
| <b>Approvals</b> | <b>Function</b>     | <b>Category</b> | <b>CRN</b>       |
| <b>ECE</b>       | Stop/Tail           | 01 2a           | 11054            |
| <b>ECE</b>       | Indicator           | 02 R1-S1        | 11054            |

### Part Number - Twin Pack

**81STI2** - 12 Volt, Blister twin pack

**80STIM2** - Multivolt 12-24V, Blister twin pack



#### Part Number

**80BSTIM** - Multivolt 12-24V, Blister single

**80BSTIMB** - Multivolt 12-24V, Bulk boxed


**80BSTIM6** - Multivolt 12-24V, 6m cable, Bulk poly bag

|                  |                             |                 |                  |
|------------------|-----------------------------|-----------------|------------------|
| <b>Function</b>  | Stop/Tail/Indicator         |                 |                  |
| <b>Size</b>      | 100mm x 100mm x 28mm        |                 |                  |
| <b>Voltage</b>   | Multivolt 12-24V            |                 |                  |
| <b>LED Qty</b>   | 24                          |                 |                  |
| <b>Cable</b>     | 40cm cable or 6 meter cable |                 |                  |
| <b>Draw</b>      | <b>Stop</b>                 | <b>Tail</b>     | <b>Indicator</b> |
| <b>@13.8V</b>    | 0.33A                       | 0.06A           | 0.31A            |
| <b>@28V</b>      | 0.25A                       | 0.04A           | 0.22A            |
| <b>Approvals</b> | <b>Function</b>             | <b>Category</b> | <b>CRN</b>       |
| <b>ADR</b>       | Stop                        | 49/00           | 35788            |
| <b>ADR</b>       | Tail                        | 49/00           | 35789            |
| <b>ADR</b>       | Indicator                   | 6/00/2A         | 35787            |

## Fitting Instructions

Surface mount onto flat surface with Indicator at top using screws supplied, run wire through 10mm hole in fixing surface. Please refer to ADR 13/00 for mounting instructions.

## Technical Drawings



## Blister Packaging

