

# 135 Series Rear Combination Lamp

- Surface or Recessed Mount
- Low Profile design
- ADR approved
- IP67 100% Waterproof
- Voltage Range 12-24 Volt
- 5 Year Warranty

ADR  
Approved

100%  
Water Proof

5 Year  
Warranty

<b>Function</b>	Stop/Tail/Indicator
<b>Size</b>	135mm x 38mm x 24mm
<b>Voltage</b>	12-24 Volt
<b>LED Qty</b>	16
<b>Cable</b>	40cm

<b>Draw</b>	<b>Stop</b>	<b>Tail</b>	<b>Ind</b>
<b>@13.8V</b>	0.12A	0.01A	0.21A
<b>@28V</b>	0.08A	0.02A	0.11A



<b>Approvals</b>	<b>Function</b>	<b>Category</b>	<b>CRN</b>
<b>ADR</b>	Stop/Tail	49/00	39847
<b>ADR</b>	Indicator	6/00 2a	39846
<b>CTA</b>	Stop/Tail/Ind	49/00, 6/00 2a	CTA-060215



Stop/Tail/Indicator - Surface Mount  
**135ARM** - Single Blister  
**135ARM/2** - Twin Blister



Stop/Tail/Indicator - Recessed Mount  
**135ARMG** - Single Blister



## Fitting Instructions

Surface mount horizontally surface mount with screws or plugs provided, run wires through back & clip lens into place. Recess mount horizontally with grommet provided, run wires through back & push lens into place, (cut out for grommet 133mm x 36mm) Refer to ADR 13/00 for mounting instructions.



All enquiries P: (03) 9466 7075 E: led@ledtech.com.au, www.ledautolamps.com

All efforts are made to ensure all information is correct and up to date, it can be subject to change without notice. All measurements are in millimeters (mm) and are not to scale.

© All LED Technologies designs are registered throughout the world. - Current as of 30/11/2021