82 Series Triples

• Low Profile Design

Surface Mounting

• ECE Australian Road Approved

• IP67 Rated

• 12 Volt or 12-24 Volt

• 5 Year Warranty

(Stop/Tail)/Indicator/Reverse **Function**

Size 281mm x 101mm x 30mm

Voltage 12 Volt Only

LED Qty 8 (Red/Amber), 16 (White)

Cable 300mm **PMMA** Lens **Bracket**

ABS

Indicator Reverse **Draw** Tail Stop @13.8V 0.1A 0.02A 0.19A 0.24A @28V 0.06A 0.02 0.08A 0.13A

Approval No. **Approvals** Function

Stop/Tail 49/00 CTA-060157 **ECE ECE** Indicator 6/00 CTA-060157 **ECE** Reverse 1/00 CTA-060157

Stop/Tail/Indicator

82BARR - 12 Volt, Single Blister, Coloured Lens



Stop/Tail/Indicator

82CARR - Single Blister, Clear Lens

ECE Approved **IP67** Protection

5 Year Warranty


Stop/Tail/Indicator/Reverse


82BARW - 12 Volt, Single Blister, Coloured Lens



Stop/Tail/Indicator/Reverse

82CARW - Single Blister, Clear Lens





Fitting Instructions

Horizontally mount bracket onto flat surface with screws provided, ensuring TOP markings are positioned above centre holes. Remove backing from 3M tape on back of lens, run wires through desired centre hole and align the locator nodule on edge of lens with the corresponding indentation on bracket. Apply firm hand pressure to ensure lamp adhesion. Repeat for each lens until all are installed securely.

